

DEWALT®

POWER GENERATORS



www.**DEWALT**.com

GUARANTEED TOUGH®

POWER GENERATORS

Quality, efficiency and high product standards are achieved through the use of modern design and manufacturing techniques, exceeding international regulations for noise and environmental pollution



Easy access fuel tap



Large, long running fuel tank



Durable metal covers



Professional quality engine



Overload protection



Tough steel frame



OPTIONALS



WHEEL KIT AND FOLDING HANDLES



LIFTING KIT



Ultra silent muffler



The perfect solution when you need a long lasting professional supply

GENERATING SET		DXGN3000E	DXGN4000E	DXGN5000E	DXGN8000E	DXGN5000E	DXGN8000E
POWER SUPPLY		SINGLE PHASE				THREE PHASE	
POWER THREE PHASE							
STAND BY POWER LTP	kW / kVA	-	-	-	-	4,8 / 6	6,3 / 7,9
CONTINUOUS POWER COP	kW / kVA	-	-	-	-	4,1 / 5,1	5,4 / 6,8
POWER SINGLE PHASE							
STAND BY POWER LTP	kW / kVA	2,5 / 2,8	3 / 3,3	4,4 / 4,9	6,1 / 6,8	3,3 / 3,6	3,5 / 3,8
CONTINUOUS POWER COP	kW / kVA	2,1 / 2,4	2,5 / 2,8	3,8 / 4,2	5,3 / 5,8	3,1 / 3,4	3,2 / 3,5
POWER SPECIFICATIONS							
VOLTAGE	Volt	230	230	230	230	400 / 230	400 / 230
FREQUENCY	Hz	50	50	50	50	50	50
POWER FACTOR	cos Φ	0,9	0,9	0,9	0,9	0,8 / 0,9	0,8 / 0,9
ENGINE							
BRAND		Honda	Honda	Honda	Honda	Honda	Honda
MODEL		GX160	GX200	GX270	GX390	GX270	GX390
FUEL		Petrol	Petrol	Petrol	Petrol	Petrol	Petrol
DISPLACEMENT	cc	163	196	270	389	270	389
SPEED	rpm	3000	3000	3000	3000	3000	3000
CYLINDER		1 inclined	1 inclined	1 inclined	1 inclined	1 inclined	1 inclined
COOLING SYSTEM		Air	Air	Air	Air	Air	Air
STARTING SYSTEM		Recoil	Recoil	Recoil	Recoil	Recoil	Recoil
CONSUMPTION							
FUEL CONSUMPTION at 75% of load	L/h	0,88	1,18	1,67	2,14	1,66	2,15
FUEL TANK CAPACITY	L	11	11	11	11	11	11
RUNNING TIME at 75% of load	h	12,5	9,32	6,59	5,14	6,63	5,12
NOISE EMISSION							
NOISE PRESSURE LEVEL at 7 mt	dB(A)	68	67	69	69	69	69
GUARANTEED SOUND POWER LEVEL	LWA dB(A)	96	95	97	97	97	97
DIMENSION AND WEIGHT							
LENGTH	mm	653	653	759	759	759	759
WIDTH	mm	465	465	532	532	532	532
HEIGHT	mm	515	515	550	550	550	550
WEIGHT (DRY)	kg	41	43	61	73	75	81
STANDARD EQUIPMENTS **							
FUEL TANK MATERIAL		Plastic	Plastic	Plastic	Plastic	Plastic	Plastic
SOCKETS		2 x 230V Schuko 16A IP54		1 x 230V Schuko 16A IP54		1 x 230 Schuko 16A IP54	
				1 x 230V CEE 16A IP44	1 x 230V CEE 32A IP44	1 x 230V CEE 16A IP44	
						1 x 400V CEE 16A IP44	
AVR - AUTOMATIC VOLTAGE REGULATOR		√	√	√	√	√	√
PROTECTIONS**							
OIL GUARD		√	√	√	√	√	√
THERMAL PROTECTION		√	√	√	√	√	√
ALTERNATOR PROTECTION	IP	23	23	23	23	23	23
OPTIONALS							
LIFTING KIT		o	o	o	o	o	o
TRANSPORTATION KIT With folding handles		o	o	o	o	o	o

- = Not available - o = Accessory available - √ = standard - ** = Other configurations and detailed specifications are available on www.pramac.com

The producer reserves the right to introduce changes to models and features without prior notice -The product images shown are for illustration purposes only and may not be an exact representation of the product.



PR INDUSTRIAL SRL

**Località il Piano,
53031 Casole d'Elsa (SI) ITALY**

Tel. +39 0577 9651

Fax +39 0577 949076

info@pramac.com

www.pramac.com

Your DeWALT® Dealer

WWW.DEWALT.com

DeWALT™ is trademark of The DeWALT Corporation and is used under license. All rights reserved. Manufactured by PRAMAC under license.
The yellow and black color scheme is used on DEWALT Power Tools and Accessories as a trademark. DEWALT reserves the right to change any deal at any time without notice. Deals available while stocks last.

Ed. 2019_En/04_2019